




You know why.

Your Ally in Panama



Magna Tyres

Mining & Earthmover



MA01

E3/L3

The E3/L3 non-directional tread pattern provides superior traction in soft underfoot.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
17.5R25	**	E3	167B	5450 kg / 5.25 bar	14.00 / 1.5	1346	457	27
		L3	182A2	8500 kg / 6.5 bar				
20.5R25	**	E3	177B	7300 kg / 5.25 kg	17.00 / 2.0	1473	533	31
		L3	193A2	11500 kg / 6.5 bar				
23.5R25	**	E3	185B	9250 kg / 5.25 bar	19.50 / 2.5	1625	609	36
		L3	201A2	14500 kg / 6.5 bar				

MA01+

E3/L3

Proven E3/L3 tread pattern optimized for a wide range of challenging construction and quarry applications.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
17.5R25	**	E3	167B	5450 kg / 5.25 bar	14.00/1.5	1350	445	27
		L3	182A2	8500 kg / 6.5 bar				
20.5R25	**	E3	177B	7300 kg / 5.25 bar	17.00/2.0	1490	520	33
		L3	193A2	11500 kg / 6.5 bar				
23.5R25	**	E3	185B	9250 kg / 5.25 bar	19.50/2.5	1615	595	36
		L3	201A2	14500 kg / 6.5 bar				
26.5R25	**	E3	193B	11500 kg / 5.25 bar	22.00/3.0	1750	675	37
		L3	209A2	18500 kg / 6.5 bar				
29.5R25	**	E3	200B	14000 kg / 5.25 bar	25.00/3.5	1875	750	43
		L3	216A2	22400 kg / 6.5 bar				

MA02

E3+/L3+

The E3+/L3+ tread pattern provides excellent traction in all off-road applications with thick undertread for improved puncture resistance.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
23.5R25	**	E3+	185B	9250 kg / 5.0 bar	19.50 / 2.5	1615	598	41
		L3+	201A2	14500 kg / 6.5bar				
26.5R25	**	E3+	193B	11500 kg / 5.0 bar	22.00 / 3.0	1754	686	41
		L3+	209A2	18450 kg / 6.5 bar				
29.5R25	**	E3+	200B	13950 kg / 5.0 bar	25.00 / 3.5	1880	737	44
		L3+	216A2	22350 kg / 6.5 bar				

MA02F

E3+

The durable and aggressive E3+ open tread design provides the tyre to grip in the most demanding surfaces.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build-up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/ressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	TKPH
29.5R29	**	E3+	202B	15000 kg / 5.25 bar	25.00/3.5	1990	770	50	348
33.25R29	**	E3+	209B	18500 kg / 5.25 bar	27.00/3.5	2065	860	45	429
37.25R35	**	E3+	218B	23600 kg / 5.25 bar	31.00/4.0	2360	940	47	545

MA02+

E3+ / L3+

The E3+/L3+, self-cleaning tread design provides excellent traction and stability on the most demanding surfaces.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build-up inside the tyre.



Tyre Size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
750/65R25	**	E3+	190B	10600 kg / 4.25 bar	24.00/3.0	1585	740	40
		L3+	202A2	15000 kg / 4.75 bar				
875/65R29	**	E3+	203B	15500 kg / 4.25 bar	27.00/3.0	1860	860	48
		L3+	214A2	21200 kg / 4.75 bar				

MA60

E3/L3

Innovative tread lugs and grooves provides powerful forward and lateral traction and superior operator comfort.

Radial E3/L3 long-lasting tread provides maximised productivity and reduced long-term operating costs.

Special rubber compound and exceptionally robust casing ensures greater resistance to damage resulting in a prolonged tyre performance.



Tyre Size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
800/80R29 33.25R29	..	E3	209B	18.500 kg / 5.25 bar	27.00/3.5	2090	845	50
		L3	225A2	29.000 kg / 6.50 bar				

M-TERRAIN

E4/L4

E4/L4 tread pattern tyre for all terrain, with excellent traction and safety characteristics. The multi-edged blocks offer improved flotation and super traction.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
20.5R25	**	E4	177B	7300 kg / 5.25 bar	17.00/2.0	1490	520	48
		L4	193A2	11500 kg / 6.50 bar				
23.5R25	**	E4	185B	9250 kg / 5.25 bar	19.50/2.5	1615	595	53
		L4	201A2	14500 kg / 6.50 bar				
26.5R25	**	E4	193B	11500 kg / 5.25 bar	22.00/3.0	1800	675	56
		L4	209A2	18500 kg / 6.50 bar				
29.5R25	**	E4	200B	14000 kg / 5.25 bar	25.00/3.5	1875	750	59
		L4	216A2	22400 kg / 6.50 bar				
750/65R25	**	E4	190B	10600 kg / 5.25 bar	24.00/3.0	1610	754	53
		L4	209A2	18500 kg / 6.25 bar				
875/65R29	**	E4	203B	15500 kg / 5.25 bar	28.00/3.5	1875	879	59
		L4	221A2	25750 kg / 6.50 bar				

M-TERRAIN+

E4/L4

Super wide non-directional tread design and open shoulder grooves offer high traction in all applications.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
775/65R29	**	E4	195B	12150 kg/ 4.25 bar	24.00/3.5	1745	770	56
		L4	213A2	20600 kg / 8.25 bar				

MA04+

E4

The E4 pattern and aggressive lug design with large blocks at tread centre provides excellent traction and braking on rough surfaces.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
14.00R25	***	E4	169B	5800 kg / 7.0 bar	10.00/1.5	1420	375	38
16.00R25	***	E4	180B	8000 kg / 8.0 bar	11.25/2.0	1550	430	44
18.00R25	***	E4	189B	10300 kg / 7.0 bar	13.00/2.5	1675	500	51
18.00R33	**	E4	191B	10900 kg / 7.0 bar	13.00/2.5	1875	500	54
21.00R33	**	E4	200B	14000 kg / 7.0 bar	15.00/3.0	1955	570	54
21.00R35	***	E4	204B	16000 kg / 8.0 bar	15.00/3.0	2005	570	61
24.00R35	**	E4	209B	18500 kg / 7.0 bar	17.00/3.5	2175	655	65
	***		212B	20000 kg / 8.0 bar	17.00/3.5			

MA04+ GIANT

E4

Aggressive extra deep tread pattern offers long even tread wear, a cooler running design and improved traction.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	TKPH				
									A1	A2	ST	B2	B1
27.00R49	**	E4	223B	27250 kg / 6.5 bar	19.50/4.0	2690	740	82	392	465	500	535	625
33.00R51	**	E4	235B	38750 kg / 6.5 bar	24.00/5.0	3030	920	95	431	496	565	634	724
37.00R57	**	E4	246B	53000 kg / 7.25 bar	27.00/6.0	3440	1050	99	682	800	880	960	1111
40.00R57	**	E4	250B	60000 kg / 7.25 bar	29.00/6.0	3560	1130	99	631	750	805	860	1006
46/90R57	**	E4	252B	63000 kg / 7.0 bar	29.00/6.0	3560	1180	98	696	816	898	980	1134
50/80R57	**	E4	257B	73000 kg / 6.0 bar	34.00/5.0	3620	1266	95	715	780	980	1180	1305
59/80R63	**	E4	268B	100000 kg / 6.0 bar	44.00/5.0	4026	1480	88	1093	1216	1476	1736	1940

M-RIGID

E4

The deep non-directional E4 tread pattern provides excellent traction & protection against cuts and damages.

All steel radial construction with an optimized load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build-up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	TKPH				
									A1	A2	ST	B2	B1
27.00R49	**	E4	223B	27250 kg / 6.5 bar	19.50/4.0	2690	740	82	392	465	500	535	625
33.00R51	**	E4	235B	38750 kg / 6.5 bar	24.00/5.0	3030	920	95	431	496	565	634	724
40.00R57	**	E4	250B	60000 kg / 7.25 bar	29.00/6.0	3560	1130	99	631	750	805	860	1006

MA09+

E4

Deep E4 tread pattern provides resistance to cutting, chipping and shock damage and enhances tyre life.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)	TKPH				
									A1	A2	ST	B2	B1
30.00R51	**	E4	230B	33500 kg / 6.5 bar	22.00/4.5	2878	845	75	456	536	588	643	744
36.00R51	**	E4	241B	46250 kg / 6.5 bar	26.00/5.0	3194	990	83	631	740	814	888	1028

MA05

L5

The extra deep L5 rock tread and reinforced shoulders and sidewalls prevent damage in severe operating conditions.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
17.5R25	**	L5	182A2	8500 kg / 6.5 bar	14.00/1.5	1397	483	65
26.5R25	**	L5	209A2	18500 kg / 6.5 bar	22.00/3.0	1803	686	91
29.5R25	**	L5	216A2	22400 kg / 6.5 bar	25.00/3.5	1905	787	100

MA07+

L5

The L5 tread pattern protects against tears, wear and cuts while providing stability, comfort and traction.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
35/65R33	***	L5	229A2	32500 kg/8.0 bar	28.00/3.5	2080	890	97

MA08

L4/L5

The massive tread blocks and aggressive L4/L5 open tread design provides outstanding grip and traction.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
20.5R25	**	L5	193A2	11500 kg / 6.5 bar	17.00/2.0	1548	521	72
23.5R25	**	L5	201A2	14500 kg / 6.5 bar	19.50/2.5	1662	592	78
26.5R25	**	L5	209A2	18500 kg / 6.5 bar	22.00/3.0	1800	665	87
29.5R25	**	L5	216A2	22400 kg / 6.5 bar	25.00/3.5	1900	720	95
29.5R29	**	L5	218A2	23600 kg / 6.5 bar	25.00/3.5	1960	750	95
35/65R33	**	L4	224A2	28000 kg / 6.5 bar	28.00/3.5	2075	880	63
35/65R33	**	L5	224A2	28000 kg / 6.5 bar	28.00/3.5	2075	880	97

MA10+

L5

Super deep open tread pattern designed for wheel loaders, dozers and grader requiring maximum traction.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load/pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
20.5R25	**	L5	193A2	11500 kg / 6.5 bar	17.00/2.0	1550	520	70
23.5R25	**	L5	201A2	14500 kg / 6.5 bar	19.50/2.5	1676	595	76
26.5R25	**	L5	209A2	18500 kg / 6.5 bar	22.00/3.0	1800	675	86
29.5R25	**	L5	216A2	22400 kg / 6.5 bar	25.00/3.5	1920	750	96

MB10

L5

Extra deep L5 tread pattern for excellent traction in the most severe circumstances.

All cross-ply construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Ply Rating	TRA code	Load index/ Speed symbol	Single max. Load /pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
20.5-25	20	L5	186A2	9500 kg / 4.50 bar	1700/2.0	1550	520	79
23.5-25	24	L5	196A2	12500 kg / 4.75 bar	19.00/2.5	1675	595	84
26.5-25	28	L5	203A2	15500 kg / 4.75 bar	22.00/3.0	1800	675	91

M-DESERT

E7

The E7 tread pattern protects against tears, wear and cuts while providing stability, comfort and traction.



All cross-ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	TT/TL	Ply rating	TRA code	Load index/ Speed symbol	Single max. Load /pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
21.00-25	TL	28	E7	186A2	9.500 kg / 4.25 bar	25.00/3.0	1654	628	15
29.5-25	TL	28	E7	188B	10.000 kg / 2.5 bar	25.00/3.5	1830	750	21.5

M-SNOW

G2/L2

Open and self cleaning tread pattern with separate tread blocks and multiple sipes for excellent traction.



All steel radial construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build-up inside the tyre.



Tyre size	Star Rating	TRA code	Load index/ Speed symbol	Single max. Load /pressure	Rim	Overall diameter (mm)	Section width (mm)	Tread depth (mm)
17.5R25	**	G2	162A8	4750 kg / 4.5 bar	14.00/1.5	1320	440	28
		L2	182A2	8500 kg / 6.5 bar				
20.5R25	**	G2	170A8	6000 kg / 4.5 bar	17.00/2.0	1484	540	31
		L2	193A2	11500 kg / 6.5 bar				
23.5R25	**	G2	179A8	7750 kg / 4.5 bar	19.50/2.5	1600	550	30
		L2	201A2	14500 kg / 6.5 bar				

Our giants

49", 51", 57", 63"

Our giant OTR tyres are especially designed for mining & earthmover applications. Our giants are the perfect fit for heavy equipment to carry heavy loads.

It has the best traction on the most difficult surfaces, such as muddy and rocky terrains. In these severe conditions, tyres need to perform optimal, even at high speeds.

Within this range we have developed different giant sizes, from 27.00R49 till 59/80R63. These giant tyres can be used on rigid dump trucks in various mining sites and is the perfect choice for your fleet.




Magna MA04+
E4

- 14.00R25
- 16.00R25
- 18.00R25
- 18.00R33
- 21.00R33
- 21.00R35
- 24.00R35



Magna MA04+
GIANT E4

- 27.00R49
- 33.00R51
- 37.00R57
- 40.00R57
- 46/90R57
- 50/80R57
- 59/80R63



Magna M-Rigid
E4

- 27.00R49
- 33.00R51
- 40.00R57



Magna MA09+
E4

- 30.00R51
- 36.00R51



Magna Tyres worldwide

▶ **MAGNA TYRES HQ**
De Kroonweg 12,
5145 NH Waalwijk
P.O. Box 436, 5140 AK Waalwijk
The Netherlands
+31 416 675 220
info@magnatyres.com

▶ **MAGNA TYRES GERMANY**
Knautnaundorfer Str. 207,
D-04249 Leipzig
Deutschland
+(49)341 - 41 29 571
info@magnatyres.de

▶ **MAGNA TYRES POLAND Sp. z o.o.**
Ul. Krakowska 48
32-064 Rudawa
Poland
+48 12 626 08 55
biuro@magnatyres.com.pl

▶ **MAGNA TYRES CANADA LTD**
100 Allstate Parkway,
#503
Markham, ON L3R 6H3
Canada
info@magnatyres.ca

▶ **MAGNA TYRES CHILE**
Orinoco 90, Piso 16
7560970 Las Condes Santiago
Chile
+56 2 29516867
info@magnatyres.cl

▶ **MAGNA TYRES SOUTH AFRICA**
Maxwell Office Park, MacMac
Building 4
Magwa Crescent, Waterfall City,
Midrand. 2191, South Africa
+27 - 100 - 055 - 774
info@magnatyres.co.za

▶ **MAGNA TYRES MIDDLE EAST & AFRICA**
RAK Free Zone, 109, BC3
PO Box: 326097, Ras al-Khamah
UAE (United Arab Emirates)
+971-7207-8814
info@magnatyres.ae

▶ **MAGNA TYRES KOREA**
Hyoshin Hispec Co. Ltd, 6th Floor
Hyun Building, 274-2, Yang-
jae-dong
Seocho-gu, Seoul, Korea
+82-2-3461-1777
info@magnatyres.kr


▶ **MAGNA TYRES ASIA LTD**
Units 1607-8, 16th Floor
Citicorp Centre
18 Whitfield Road
Causeway Bay
Hong Kong

▶ **MAGNA TYRES TECHNICAL SERVICE (SHANGHAI) CO, LTD**
Room 1504
No. 578 Yingkou Road
Yangpu District
Shanghai
China

▶ **MAGNA TYRES SINGAPORE**
Duo Towers – office 815, 3 Fraser
Street Singapore 189352
Singapore
+65 6828 1473
info@magnatyres.sg

▶ **MAGNA TYRES USA**
3281 E Guasti Road
Suite 320
Ontario, CA 91761
United States
+1 (954) 492 7974
info@magnatyres.us

▶ **MAGNA TYRES CZECH S.R.O**
Tuřanka 1519/115a
627 00 Brno Czech Republic
+420 603 911 163
info@magnatyres.cz



DISTRIBUTOR IN PANAMA
info@iporservices.com
+507 6152-2377
Free Zone -Warehouse
Panama - Rep. of Panama



