



Your ally in Panama

Magna Tyres

Port & Terminal



MB01 / MB01S

IND-3 / IND-4

Improved traction and performance through non-directional IND-3/IND-4 tread design.

All cross ply construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	Ply Rating	TRA code	Single max. load (kg)				Pressure (bar)	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
				Static	5 km/h	10 km/h	25 km/h					
16.00-25	MB01	32	IND-3	22500	18100	16900	15600	10.00	11.25/2.0	1485	1448	32
18.00-25	MB01	40	IND-4	31500	25400	23600	21900	10.00	13.00/2.5	1610	500	55
21.00-25	MB01	40	IND-3	36400	29300	27300	25300	10.00	15.00/3.0	1759	585	38
18.00-33	MB01	40	IND-4	37000	29900	27800	25700	10.00	13.00/2.5	1877	498	65
21.00-35	MB01	40	IND-3	43700	35200	32800	30400	10.00	15.00/3.0	2005	570	38
18.00-25	MB01S	40	IND-4	31500	25400	23600	21900	10.00	13.00/2.5	1675	500	60

M-STACKER/+

IND-4

Deep, wide tread grooves supports easier turning by reducing stress in tread blocks.

All cross ply construction with an improved load performance and enhanced operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre Size	Pattern	Ply Rating	TRA code	Rim	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)	Load Capacity (kg)		
								Speed (km/h)	Load wheel	Steering wheel
18.00-25	M-STACKER	40	IND-4	13.00/2.5	1680	480	50	25	21.900	17.500
								10	23.600	18.900
								0	31.500	25.200
18.00-25	M-STACKER+	40	IND-4	13.00/2.5	1650	480	70	25	21.900	17.500
								10	23.600	18.900
								0	31.500	25.200

MB02

IND-3 / IND-4

Improved traction and performance through non-directional IND-3/IND-4 tread design.

All cross ply construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	TL/TT	TRA code	Ply Rating	Single max. load (kg)				Pressure (bar)	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
				Static	5 km/h	10 km/h	25 km/h					
11.00-20	TT	IND-3	18	10030	7615	6920	5830	8.5	8.0	1085	293	22
12.00-24	TL/TT	IND-4	24	12300	10800	9300	7100	10.0	8.5	1245	315	35
14.00-24	TL	IND-4	28	18000	14500	13500	12000	10.0	10.0	1370	375	50
18.00-25	TL	IND-3	40	30600	24600	22900	21200	11.4	13.00/2.5	1615	510	43
18.00-25	TL	IND-4	40	30600	24600	22900	21200	10.0	13.00/2.5	1675	515	55
18.00-33	TL	IND-4	40	38200	30700	28600	26500	10.0	13.00/2.5	1875	500	70

MB300 / MB300+ IND-3

Improved traction and performance through deep nondirectional tread design.

All cross ply construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	TT/TL	Ply Rating	TRA code	Loading capacity (kg)	Pressure (bar)	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
14.00-24	MB300	TT	28	IND-3	10000	9.25	10.00	1370	375	26
14.00-24	MB300+	TT/TL	28	IND-3	12000	10.0	10.00	1370	375	30

MB800

Self-cleaning and non-directional tread pattern.



All cross ply construction. Improved protector plies optimize load performance and operator comfort.



New improved technology of the high-tech casing reduces heat build up inside the tyre.



Load capacity (kg)

Tyre size	Ply Rating	Drive wheel 25 km/h	Steer wheel 25 km/h	Drive wheel 35 km/h	Steer wheel 35 km/h	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
5.00-8	10	1150	970	1065	850	3.50	470	137	11
6.00-9	10	1505	1275	1400	1120	4.00	540	160	12
6.50-10	12	1895	1600	1765	1410	5.00	570	150	13
7.00-12	14	2590	2190	2405	1925	5.00	676	190	14
8.25-15	14	3775	3185	3505	2800	6.50	710	220	18
28x9-15	14	3050	2575	2835	2265	7.00	710	220	18
250-15	18	4110	3470	3820	3050	7.50	735	250	18
300-15	20	5940	4990	5485	4375	8.00	840	300	20
10.00-20	20	6950	5800	6500	5150	7.50	1074	277	22
12.00-20	20	7750	6510	7207	5735	8.50	1145	315	24
12.00-20	24	8500	7140	7905	6290	8.50	1145	260	26

MR800+

IND-4

Engineered with special tread compound to run cool, fight rapid wear and deliver remarkable stability.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Star Rating	TRA code	Load/speed index	Max Load capacity (kg)	Pressure (bar)	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
9.00R20	**	IND-4	160A5	4.500	10.0	7.00	1030	170	33
10.00R20	**	IND-4	166A5	5.300	10.0	7.00	1055	280	35
11.00R20	**	IND-4	170A5	6.000	10.0	8.00	1090	294	38
12.00R20	**	IND-4	176A5	7.100	10.0	8.50	1120	305	40
12.00R24	***	IND-4	178A5	7.500	10.0	8.50	1222	305	40
14.00R24	***	IND-4	193A5	11.500	10.0	10.00	1408	386	65
16.00R25	***	IND-4	200A5	14.000	10.0	11.25/2.0	1510	420	71
18.00R25	***	IND-4	207A5	17.500	10.0	13.00	1648	512	65
18.00R33	***	IND-4	219A5	24.300	10.0	13.00	1828	475	70

M-TERMINAL

IND-3

Developed with a deep tread profile and industrial casing, the tyre offers high resistance to damage and punctures.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Load/speed index	Single max. load (kg)	Pressure (bar)	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
280/75R22.5	168A8	5600	10.0	7.50 / 8.25	988	273	32
310/80R22.5	175A8	6900	10.0	8.25 / 9.00	1078	300	32

M-STRADDLE/+

IND-4

Heavy-duty sidewalls in combination with the deep and ribbed tread pattern guarantee excellent resistance to damage and impacts.

All steel radial construction. Improved protector plies optimize load performance and operator comfort.

New improved technology of the high-tech casing reduces heat build up inside the tyre.



Tyre size	Pattern	TRA code	Load symbol	Load/speed index	Single max. load (kg)	Pressure (bar)	Rim	Overall Diameter (mm)	Section Width (mm)	Tread depth (mm)
16.00R25	M-Straddle	IND-4	**	202A7	15000	10.0	11.25/2.0	1550	430	50
16.00R25	M-Straddle+	IND-4	**	202A7	15000	10.0	11.25/2.0	1550	430	48
480/95R25	M-Straddle+	IND-4	**	206A5	17000	10.0	13.00/2.5	1535	455	50